

Better than fresh air.™

High Efficiency Air Filtration for Furnace Mount Housings



Removes 99% of Respirable Suspended Particles (RSPs) • Installs In Minutes • Energy Efficient • Easy To Maintain

We've Made IAQ Fast, Simple & Profitable.

AspenAir offers the only practical furnace mountable systems that provide true high-efficiency air filtration. Our systems deliver 24KV of safe cleaning power while using less than 2 watts to remove 99% of the Respirable Suspended Particles (RSP) from the air, which is up to 20 times the amount removed by conventional EACs. Install AspenAir Inside with new systems or retrofit existing systems and increase your IAQ revenues and margins.

Why AspenAir Inside is the Contractor's Choice...

- * Simple to sell – low cost & least complicated option available for “clean room” quality indoor air.
- * High efficiency performance – 99% to 0.1 microns (IBR Laboratories).
- * Low static pressure – 0.11” w.g. @ 1200 CFM (RTI International).
- * Product flexibility – 4 “standard” sizes with new SlimLine design, 3.75” nominal width.
- * Our SlimLine housing – 4.75” nominal width – ideal when space is limited (sold separately).
- * Quick, simple & easy installations – takes minutes, not hours, using low voltage wiring.
- * QuikTrak RetroKit - retrofits virtually any existing EAC or media housing (comes standard).
- * Quick, simple & easy maintenance – takes three minutes or less once or twice a year.
- * Easy to handle – lightweight & without sharp edges to cut fingers or damage property.
- * Keeps customers – aligns with service agreements to lock in customers.
- * Green Product – uses 95% less electricity than conventional EACs & low static pressure helps optimize air handler efficiency.



Furnace Mount
Fits standard housings

Why Homeowners Love AspenAir Inside...

- * Fast, non-invasive installation.
- * Healthy indoor air without the cost & complexity of competitor's systems.
- * Maintenance is quick, easy, infrequent & inexpensive.
- * No sparking, arcing, or harmful ozone emissions.
- * Simple, visible & easy to understand performance indicator.
- * Solid construction & “no hassle” 5-year warranty provides assurance of years of trouble-free performance.
- * Reduced carbon footprint due to low static pressure & low energy use – less than 2 watts.



For more information, please contact us at:
888.326.0976 or visit us at www.AspenAirInside.com



DEALER DESIGN
AWARDS

the NEWS | 2 0 0 8

AspenAir Product Models

MADE IN THE USA

Furnace Mount Models

Nominal Size*	Dimensions*	Model
16 X 20 X 3.75	16 X 20.25 X 3.75	FM241620
16 X 24 X 3.75	16 X 24.25 X 3.75	FM241624
20 X 20 X 3.75	20 X 20.25 X 3.75	FM242020
20 X 24 X 3.75	20 X 24.25 X 3.75	FM242024

* Nominal and Dimension sizes are measured in inches.

Furnace Mount Notes:

1. Units are 3.75 inches nominal width.
2. Units come standard 24VAC.
3. One unit shipped per carton.
4. QuikTrak RetroKit – comes standard.
5. SlimLine housing – 4.75" nominal width – sold separately.

Specifications	Filter Grille Series (FG)
Rated Air Flow (Rated Face Velocity: 500 FPM)	16 X 20—1200 CFM 16 X 24 } 1400 CFM 20 X 20 } 20 X 24—2000 CFM
Initial Pressure Drop	0.25 in. w.g. @ Rated Air Flow
Max Pressure Drop	1.0 in. w.g. @ Rated Air Flow
Electrical Input	Class 2, 24VAC
Electrical Output	24,000 VDC (Nominal)
Weight	8 - 10 lbs (w/o housing)
Power Consumption	2.0 Watts Max

QuikTrak RetroKit



A competitor's housing with AspenAir's RetroKit tracks.



AspenAir system slides into place.



Simple and fast retrofit saves time and money.

For more information, please contact us at:
888.326.0976 or visit us at www.AspenAirInside.com