

Broan SmartSense®

INTELLIGENT VENTILATION SYSTEM

SMSK102 & SMSK103 KITS

Improve air quality throughout the home automatically and efficiently - a smart solution to home ventilation.

FEATURES


- Removes pollutants such as house hold cleaners, VOC's, carbon dioxide/monoxide, and off-gassing from building materials, carpets and other furnishings
- Helps remove gases and particles that are not trapped by any filtration unit
- Program a single control for a ventilation rate to match the size of the home
- Automatically adjusts total run-time based on square footage and number of bedrooms
- Optimizes energy usage by monitoring normal fan operation and adjusting ventilation time as needed
- Continuously monitors and if necessary, activates Broan Ultra Silent fans located in different locations within the home – day and night
- No control wiring required – controls communicate over existing home power wires
- Uses less than 50 watts during ventilation cycles – in most installations, only one fan is running at a time
- More cost effective and energy efficient than most other ventilation strategies
- Broan Ultra Silent™ fans operate at a barely audible 0.3 (80 CFM fans) or 0.9 Sones (110 CFM fans)
- Easy installation of fans in the ceiling, vented to the exterior using 6-inch duct
- 2- and 3-fan kits can be combined in to a system that can recognize 10 fans
- Meets ASHRAE 62 – related ventilation requirements



Broan SmartSense® uses INSTEON™, a powerful, wireless home control technology


INSTEON
ENABLED

Broan-NuTone LLC, 926 West State Street, Hartford, WI 53027 (1-800-637-1453)



80 CFM FAN (Model QTxE080)
110 CFM FAN (Model QTxE110)

[\(see fan spec sheet\)](#)



CONTROL
(Fits deep single-gang electrical box)



PHASE COUPLER
(Fits deep single-gang electrical box)

SMSK102 2-FAN KIT

Contains:
1 - 110 CFM Fan (Model QTxE110)
1 - 80 CFM Fan (Model QTxE080)
2 - SmartSense® Controls
1 - Phase Coupler

SMSK103 3-FAN KIT

Contains:
1 - 110 CFM Fan (Model QTxE110)
2 - 80 CFM Fans (Model QTxE080)
3 - SmartSense® Controls
1 - Phase Coupler

CONTROL SPECIFICATIONS

Paddle Type: True rocker action
Color: White Paddle & Trim Frame
Almond Paddle & Trim Frame included
Conditions: Indoor, 40° to 104° F, up to 85% relative humidity
Supply Voltage: 120 VAC +/- 10%, 60 Hz, single phase
Max. Load: 480 Watts incandescent, 13A resistive
Certification: Safety tested for use in USA and Canada (ETL #3017581)

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date

Broan SmartSense®

INTELLIGENT VENTILATION SYSTEM

SMSK102 & SMSK103 KITS

Recommended rooms for fans include:

- One for each Bathroom, Watercloset, or Shower Stall
- Laundry Room
- Rec Room
- Workshop
- Exercise Room
- Home Office
- Playroom

INSTEON™

POWERLINE PHYSICAL LAYER PROPERTIES

Frequency: 131.65 KHz
Modulation: BPSK
Min. Transmit Level: 3.16 Vpp into 5 Ohms
Min. Receive Level: 10 mV
Phase Bridging: INSTEON™ RF or hardware

**RECOMMENDED CONTINUOUS VENTILATION RATE
IN CFM (cubic feet per minute)**

Home Square Footage	Number of Bedrooms				
	0 - 1	2 - 3	4 - 5	6 - 7	> 7
< 1500	30	45	60	75	90
1501 - 3000	45	60	75	90	105
3001 - 4500	60	75	90	105	120
4501 - 6000	75	90	105	120	135
6001 - 7500	90	105	120	135	150
> 7500	105	120	135	150	165

