

PROMAX® RG5410EX

Refrigerant Recovery Machine



Experienced HVAC/R professionals understand that time is money, and the more time they can save doing a job, the more money they make at the end of the day. The new RG5410EX refrigerant recovery machine from Promax® is specifically designed to save time and money.

The “EX” is for the extreme upgrades we added to the popular RG5410A recovery machine. For example, our high efficiency 1/2 hp motor drives a redesigned compressor that increases volume flow by 20%, saving time spent on each recovery job.

We also improved the performance of the extra-large condenser, and “beefed-up” the inside of the machine, adding heavy-duty components to deliver maximum performance under the harshest conditions. Like its predecessor, the RG5410EX is built to last – and that saves money.

**EXTREME
PERFORMANCE**

PROMAX[®] RG5410EX

Refrigerant Recovery Machine



RG5410EX Key Features

- Extremely fast recovery of all commonly used CFC, HFC and HCFC refrigerants, including R410A.
- An automatic low-pressure cut-off switch turns the machine off at 15" of vacuum, eliminating unnecessary wear and tear on the machine.
- Auto-purge helps clear any residual refrigerant, leaving the machine "ready to go" for the next service call.
- Padded handle grip makes carrying the machine to job sites easier and more comfortable.

Technical Specifications
Per ARI 740
Approved for use with:

R-12	R-407C
R-22	R-407D
R-134A	R-408A
R-401A	R-409A
R-401B	R-410A
R-401C	R-411A
R-402B	R-412A
R-404A	R-500
R-406A	R-502
R-407A	R-507
R-407B	R-509

RG5410EX Specifications

Recovery capabilities	Vapor, liquid, push/pull
Compressor	Oil-less, 100:1 compression ratio
Motor	Direct drive _ hp, high efficiency
Size	19" L x 13" H x 9" W
Weight	34 lbs.
Electrical	110-125 VAC, 60 Hz
Approvals	ARI-740, UL, CE and TUV - pending
Warranty	1-year over counter exchange

Recovery Ratings per UL

	lbs./min			kg/min		
	Vapor	Liquid	Push/Pull	Vapor	Liquid	Push/Pull
R-12	.41	4.77	14.50	.18	2.17	6.59
R-22	.41	4.77	14.50	.18	2.17	6.59
R-134A	.32	4.14	11.70	.14	1.80	5.32
R-407C	.34	4.78	11.40	.15	2.17	5.18
R-410A	.44	5.13	14.10	.20	5.13	6.41

06-92 ©2006 SPX Corporation. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Product shipped may differ from photo(s) shown.

UL Certified
Per ARI Standard 740-98.
To meet or exceed EPA
regulations. Refrigerant Recovery
Machine 8EA7.

