

Time to Think **GREEN** about **CRITICAL** Humidity needs...

A quality fog distribution solution for low-ceiling applications

No compressed air

36-month Warranty

All stainless steel wetted components

Fan shuts OFF when fogging stops

Check-valve on each nozzle

Fan-forced mixing of fog within the space

6-nozzle High-pressure Fog-Fan is simple to install, uses little energy and atomizes 83 pounds-per-hour.

Weight: 35 pounds (15.8kg)

Color: White, Black, Red

Output: 9.9 GPH (37.6 LPH)

Fuse: Slow blow

Power ON Lamp: Red

Finish: Powder Coat

Voltage: 120/220 VAC @ 2A

Suspension Chains: 36in/1m

Nozzles: Stainless

Nozzle Anti-Drip Valve: Yes

Overall Diameter: 19 in/48 cm

ON/OFF: Water-Press. Sensor

Isolation Hose: 36 in (1 meter)




New for 2008

A quality fog device with outstanding design characteristics. Capable of pushing billions of fogged particles into all areas of your facility for rapid, uniform evaporation & fast recovery from decreasing humidity trends.

High-pressure water is supplied by our low-speed Cold Fog® pump system, and FOG-FAN units arrive on-site totally assembled; just attach electric and water. We operate with less energy consumption than most other methods and our VFD technology, **standard on all COLD FOG pump systems**, guarantees a 'soft-start' on every pump cycle. And COLD FOG systems only come up to the lowest possible operating RPM's needed to maintain your preset operating pressure.

Our Direct-Drive systems eliminate old fashioned belts and pulleys, operate at less speed, less noise with less vibration. Our electronics are standard with finger-safe components and all components are mounted within water-tight, dust-tight, corrosion-proof enclosures. Specified worldwide for critical cleanroom humidification whenever $\pm 1\%$ accuracy is a must.



**ATOMIZING
SYSTEMS INC**

Manufacturers of **COLD FOG®** Systems

1 Hollywood Avenue
Ho-Ho-Kus, NJ 07423-1433 USA
Tel 201-447-1222 Fax 201-447-6932
email: atomizingsystems@coldfog.com